according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 1 of 11

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

103 Penetrating oil MP10300400AB

UFI: T583-D0UQ-000E-28AT

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### Use of the substance/mixture

rust remover

## 1.3. Details of the supplier of the safety data sheet

Company name: TUNAP GmbH & Co. KG
Street: Buergermeister-Seidl-Strasse 2
Place: D-82515 Wolfratshausen

Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171/1600-40

e-mail: sdb@tunap.com Internet: www.tunap.com

1.4. Emergency telephone 111 NHS (National Health Service)

number:

## **SECTION 2: Hazards identification**

# 2.1. Classification of the substance or mixture

## **GB CLP Regulation**

Hazard categories: Aerosol: Aerosol 1

Aspiration hazard: Asp. Tox. 1

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated. May be fatal if swallowed and enters airways.

## 2.2. Label elements

## **GB CLP Regulation**

Signal word: Danger

Pictograms:



### **Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

# **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

## Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

# 2.3. Other hazards

according to UK REACH Regulation

# 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 2 of 11

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition/information on ingredients**

## 3.2. Mixtures

### Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	GHS Classification	•	•		
64742-48-9	Hydrocarbons, C10-C13, n-alkar	es, isoalkanes, cyclics, <2% arom	atics	50 - <= 100 %	
	918-481-9		01-2119457273-39		
	Asp. Tox. 1; H304 EUH066	•			
75-28-5	isobutane	25 - < 50 %			
	200-857-2	601-004-00-0	01-2119485395-27		
	Flam. Gas 1, Liquefied gas; H22				
74-98-6	propane	3 - < 5 %			
	200-827-9	601-003-00-5	01-2119486944-21		
	Flam. Gas 1, Liquefied gas; H220 H280				
106-97-8	butane				
	203-448-7	601-004-00-0	01-2119474691-32		
	Flam. Gas 1, Liquefied gas; H220 H280				

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits. M-factors and ATE

CAS No	EC No	Chemical name			
	Specific Conc. L	Limits, M-factors and ATE			
64742-48-9	918-481-9	918-481-9 Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics			
	inhalation: LC5 mg/kg	0 = 4951 mg/l (vapours); dermal: LD50 = >3160 mg/kg; oral: LD50 = >8000			
75-28-5	200-857-2	isobutane	25 - < 50 %		
	inhalation: LC50 = 1237 mg/l (vapours)				
106-97-8	203-448-7	butane	1 - < 3 %		
	inhalation: LC50 = 658 ppm (gases)				

## Labelling for contents according to Regulation (EC) No 648/2004

## **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

# **General information**

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

## After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

## After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse. In all cases of doubt, or when symptoms persist, seek medical advice.

<sup>&</sup>gt;= 30 % aliphatic hydrocarbons.

according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 3 of 11

### After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

### After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

### 4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

### Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

## Unsuitable extinguishing media

Full water jet

### 5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

#### 5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

### Additional information

Danger of bursting container.

### **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

## General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

## 6.3. Methods and material for containment and cleaning up

### Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

## 6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Observe instructions for use.

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point

according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 4 of 11

of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

## Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

### Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

## Further information on handling

Avoid contact with skin and eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

## Requirements for storage rooms and vessels

Keep container tightly closed. Observe legal regulations and provisions.

### Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

### Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

## 7.3. Specific end use(s)

No information available.

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## **Exposure limits (EH40)**

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

### Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B)

Urine (U)

# 8.2. Exposure controls

## Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

## Individual protection measures, such as personal protective equipment

### Eye/face protection

Suitable eye protection: Tightly sealed safety glasses.

**DIN EN 166** 

## **Hand protection**

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous

according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Product code: 1101050 Revision date: 20.09.2021 Page 5 of 11

substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm

**EN ISO 374** 

## Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

### Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

When exceeding the relevant workplace exposure limits, note the following:

Suitable respiratory protective equipment: Combination filter device (DIN EN 141)...

Filtering device with filter or ventilator filtering device of type: AX

Observe the wear time limits as specified by the manufacturer.

Observe legal regulations and provisions.

## **Environmental exposure controls**

Observe legal regulations and provisions.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol Colour: colourless Odour: weak

Test method

Changes in the physical state

Melting point/freezing point: not determined Boiling point or initial boiling point and -40 °C

boiling range:

Flash point: > 61 °C

**Flammability** 

Solid/liquid: not applicable not applicable Gas: not determined Lower explosion limits: Upper explosion limits: 9.4

Self-ignition temperature

Solid: not applicable Gas: not applicable Decomposition temperature: not determined

pH-Value (at 20 °C): not determined DIN 19268

Viscosity / kinematic: 1,3 mm<sup>2</sup>/s

Water solubility: The study does not need to be conducted

because the substance is known to be insoluble in water.

Solubility in other solvents

not determined

Partition coefficient n-octanol/water: not determined Vapour pressure: not determined

0,792 g/cm3 DIN 51757 Density (at 20 °C):

Relative vapour density: not determined

according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 6 of 11

### 9.2. Other information

## Information with regard to physical hazard classes

Oxidizing properties

Not oxidising.

## Other safety characteristics

Solid content: not determined Evaporation rate: not determined

### **Further Information**

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

## **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

Extremely flammable aerosol.

### 10.2. Chemical stability

The product is stable under normal conditions.

## 10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

### 10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

## 10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

### 10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

## **Further information**

Do not mix with other chemicals.

## **SECTION 11: Toxicological information**

## 11.1. Information on hazard classes as defined in GB CLP Regulation

## Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

### **Acute toxicity**

Based on available data, the classification criteria are not met.

according to UK REACH Regulation

# 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 7 of 11

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-48-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics					
	oral	LD50 mg/kg	>8000	Rat		
	dermal	LD50 mg/kg	>3160	Rabbit		
	inhalation (4 h) vapour	LC50	4951 mg/l	Rat		
75-28-5	isobutane					
	inhalation vapour	LC50	1237 mg/l	Mouse.		
106-97-8	butane					
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS	

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

## Sensitising effects

Based on available data, the classification criteria are not met.

## Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

No indication of human carcinogenicity.

No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

# STOT-single exposure

Based on available data, the classification criteria are not met.

## STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

## **Aspiration hazard**

May be fatal if swallowed and enters airways.

# Specific effects in experiment on an animal

No information available.

## Additional information on tests

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

# **SECTION 12: Ecological information**

# 12.1. Toxicity

There are no data available on the mixture itself.

according to UK REACH Regulation

# 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 8 of 11

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
64742-48-9	Hydrocarbons, C10-C13,	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics						
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)			
	Acute algae toxicity	ErC50 mg/l	>1000	96 h	Scenedesmus subspicatus			
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna			
75-28-5	isobutane							
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
74-98-6	propane							
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
106-97-8	butane							
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo	
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.	

# 12.2. Persistence and degradability

The product has not been tested.

# 12.3. Bioaccumulative potential

The product has not been tested.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09

# 12.4. Mobility in soil

The product has not been tested.

# 12.5. Results of PBT and vPvB assessment

according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 9 of 11

The product has not been tested.

### 12.7. Other adverse effects

No information available.

#### **Further information**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

### **SECTION 13: Disposal considerations**

### 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

### List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

### List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and

discarded chemicals; gases in pressure containers (including halons) containing hazardous

substances; hazardous waste

## List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately

collected municipal packaging waste); metallic packaging

## **SECTION 14: Transport information**

### Land transport (ADR/RID)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity:

Excepted quantity:

Transport category:

Tunnel restriction code:

D

Inland waterways transport (ADN)

**14.1. UN number or ID number:** UN 1950 **14.2. UN proper shipping name:** AEROSOLS

14.3. Transport hazard class(es):214.4. Packing group:-Hazard label:2.1Classification code:5F

Special Provisions: 190 327 344 625

Limited quantity: 1 L Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950

according to UK REACH Regulation

103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 10 of 11

14.2. UN proper shipping name: AEROSOLS

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1Marine pollutant:no

Special Provisions: 63, 190, 277, 327, 344, 381,959

Limited quantity: 1000 mL Excepted quantity: E0 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950

**14.2. UN proper shipping name:** AEROSOLS, flammable

14.3. Transport hazard class(es):2.114.4. Packing group:-Hazard label:2.1

Special Provisions: A145 A167 A802

Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0

IATA-packing instructions - Passenger:203IATA-max. quantity - Passenger:75 kgIATA-packing instructions - Cargo:203IATA-max. quantity - Cargo:150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

# **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Additional information

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Aerosol directive (75/324/EEC)

**National regulatory information** 

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile

work protection guideline' (94/33/EC).

Water hazard class (D): 2 - obviously hazardous to water

## **SECTION 16: Other information**

### Changes

according to UK REACH Regulation

## 103 Penetrating oil MP10300400AB

Revision date: 20.09.2021 Product code: 1101050 Page 11 of 11

This data sheet contains changes from the previous version in section(s): 2,3,6,9,11.

### Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA: International Air Transport Association

IMDG: International Maritime Code for Dangerous Goods

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level

WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average

ATE: Acute Toxicity Estimate

STEL (EC) Short Term Exposure Limit

LC50: Lethal Concentration

EC50: half maximal Effective Concentration

ErC50: means EC50 in terms of reduction of growth rate

## Classification for mixtures and used evaluation method according to GB CLP Regulation

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method

# Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

## **Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)