according to UK REACH Regulation

number: SECTION 2: Hazards identification 2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated.	Page 1 of 11
902 Synthetic Oil Fluid MP90200400AB UFI: Q8F2-M0PK-500W-78C3 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture Lubricant 1.3. Details of the supplier of the safety data sheet Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 Telefax:+49 (0) 8171 e-mail: sdb@tunap.com Internet: www.tunap.com Internet: www.tunap.com Internet: Www.tunap.com SECTION 2: Hazards identification SECTION 2: Hazards identification Mazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.1. Label elements	
UFI: Q8F2-M0PK-500W-78C3 1.2. Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture Lubricant 1.3. Details of the supplier of the safety data sheet Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 Telefax:+49 (0) 8171 e-mail: sdb@tunap.com Internet: www.tunap.com Internet: www.tunap.com Internet: Www.tunap.com SECTION 2: Hazards identification 2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
Use of the substance/mixture Lubricant 1.3. Details of the supplier of the safety data sheet Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification SECTION 2: Hazards identification GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 22. Label elements	
Use of the substance/mixture Lubricant 1.3. Details of the supplier of the safety data sheet Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification SECTION 2: Hazards identification GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 22. Label elements	
1.3. Details of the supplier of the safety data sheet Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification 2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Pressurised container: May burst if heated.	
Company name: TUNAP GmbH & Co. KG Street: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification SECTION 2: Hazards identification GB CLP Regulation Hazard categories: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.1. Label elements	
Stret: Buergermeister-Seidl-Strasse 2 Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification 21. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. Pressurised container: May burst if heated.	
Place: D-82515 Wolfratshausen Telephone: +49 (0) 8171/1600-0 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification SECTION 2: Hazards identification Image: Comparison of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 22. Label elements Extremets	
Telephone: +49 (0) 8171/1600-0 Telefax: +49 (0) 8171 e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone_number: 111 NHS (National Health Service) SECTION 2: Hazards identification 111 NHS (National Health Service) SECTION 2: Hazards identification Image: Comparison of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.1. Label elements Statements:	
e-mail: sdb@tunap.com Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification SECTION 2: Hazards identification 2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.1. Label elements	
Internet: www.tunap.com 1.4. Emergency telephone 111 NHS (National Health Service) number: 111 NHS (National Health Service) SECTION 2: Hazards identification SECTION 2: Hazards identification GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.1. Label elements	/1600-40
1.4. Emergency telephone 111 NHS (National Health Service) number: SECTION 2: Hazards identification 21. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.1. Label elements	
number: SECTION 2: Hazards identification 2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
SECTION 2: Hazards identification 2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
2.1. Classification of the substance or mixture GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
GB CLP Regulation Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
Hazard categories: Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
Aerosol: Aerosol 1 Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
Hazard Statements: Extremely flammable aerosol. Pressurised container: May burst if heated. 2.2. Label elements	
Pressurised container: May burst if heated. 2.2. Label elements	
Pressurised container: May burst if heated. <u>2.2. Label elements</u>	
Signal word: Danger	
Pictograms:	

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P260	Do not breathe spray.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear eye protection/face protection.
P251	Do not pierce or burn, even after use.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 2 of 11

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification	·	·	
75-28-5	isobutane			50 - <= 100 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Liquefied	gas; H220 H280		
68037-01-4	Dec-1-ene, homopolym	er, hydrogenated		25 - < 50 %
	500-183-1		01-2119486452-34	
	Asp. Tox. 1; H304			
74-98-6	propane	5 - < 10 %		
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied			
106-97-8	butane			1 - < 3 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied			
192268-65-8	A mixture of: triphenylth	0.1 - < 1 %		
	421-820-9	607-501-00-9	01-2119480426-35	
	Repr. 2, Aquatic Chroni			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name					
	Specific Conc.	pecific Conc. Limits, M-factors and ATE					
75-28-5	200-857-2	isobutane	50 - <= 100 %				
	inhalation: LCS	50 = 1237 mg/l (vapours)					
68037-01-4	500-183-1	Dec-1-ene, homopolymer, hydrogenated	25 - < 50 %				
	inhalation: LC50 = > 5,2 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg						
106-97-8	203-448-7	butane	1 - < 3 %				
	inhalation: LC	inhalation: LC50 = 658 ppm (gases)					
192268-65-8	421-820-9	A mixture of: triphenylthiophosphate and tertiary butylated phenyl derivatives	0.1 - < 1 %				
	inhalation: LCs mg/kg	50 = >5 mg/l (dusts or mists); dermal: LD50 = >2000 mg/kg; oral: LD50 = >2000					

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove persons to safety. Never give anything by mouth to an unconscious person or a person with cramps.

After inhalation

Remove person to fresh air and keep comfortable for breathing. In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with skin

Wash with plenty of water and soap. Take off immediately all contaminated clothing and wash it before reuse.

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 3 of 11

In all cases of doubt, or when symptoms persist, seek medical advice.

After contact with eyes

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Call a physician in any case!

4.2. Most important symptoms and effects, both acute and delayed

Headache, nausea, dizziness, fatigue, skin irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Call a POISON CENTER. Symptoms can occur only after several hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Foam. Carbon dioxide (CO2). Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Move undamaged containers from immediate hazard area if it can be done safely. In case of fire: Wear self-contained breathing apparatus.

Additional information

Danger of bursting container.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Remove all sources of ignition. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protection equipment.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Ensure all waste water is collected and treated via a waste water treatment plant.

6.3. Methods and material for containment and cleaning up

Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Observe instructions for use.

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 4 of 11

Dust must be exhausted directly at the point of origin. Vapours/aerosols must be exhausted directly at the point of origin. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

When using do not eat, drink, smoke, sniff.

Wear personal protection equipment (refer to section 8).

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Heating causes rise in pressure with risk of bursting.

Advice on general occupational hygiene

Avoid exposure. Wear suitable protective clothing. Draw up and observe skin protection programme.

Further information on handling

Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Observe legal regulations and provisions.

Hints on joint storage

Do not store together with: Oxidizing agents. Pyrophoric or self-heating substances. Food and feedingstuffs.

Further information on storage conditions

Protect from frost. Protect from direct sunlight. Store in a cool dry place. Observe legal regulations and provisions.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL

Additional advice on limit values

a no restriction

b End of exposure or end of shift

c at long-term exposure:

d before next shift

blood (B) Urine (U)

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection: Tightly sealed safety glasses. DIN EN 166

Hand protection

Protect skin by using skin protective cream. When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 5 of 11

chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) Breakthrough time: 480min

Thickness of the glove material 0,45 mm EN ISO 374

Skin protection

Wear suitable protective clothing. Take off immediately all contaminated clothing and wash it before reuse.

Respiratory protection

Wear breathing apparatus if exposed to vapours/dusts/aerosols. When exceeding the relevant workplace exposure limits, note the following: Suitable respiratory protective equipment: Combination filter device (DIN EN 141).. Filtering device with filter or ventilator filtering device of type: AX Observe the wear time limits as specified by the manufacturer. Observe legal regulations and provisions.

Environmental exposure controls

Observe legal regulations and provisions.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

1. Information on basic physical and che	emical properties	
Physical state:	Aerosol	
Colour:	colourless	
Odour:	mild	
		Test method
Changes in the physical state		
Melting point/freezing point:	not determined	
Boiling point or initial boiling point and boiling range:	-42 °C	
Flash point:	-80 °C	
Flammability Solid/liquid: Gas:	not applicable not applicable	
Lower explosion limits:	1,5	
Upper explosion limits:	9,4	
Self-ignition temperature Solid: Gas:	not applicable not applicable	
Decomposition temperature:	not determined	
pH-Value (at 20 °C):	not determined	DIN 19268
Water solubility:	The study does not need to be conducted because the substance is known to be insoluble in water.	
Solubility in other solvents not determined		
Partition coefficient n-octanol/water:	not determined	
Vapour pressure:	not determined	
Density (at 20 °C):	0,828 g/cm³	DIN 51757
Relative vapour density:	not determined	
ining Net 4.00 - Depleters upging 4.00		

Page 6 of 11

Safety Data Sheet

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

9.2. Other information

Information with regard to physical hazard classes

Oxidizing properties Not oxidising.

Other safety characteristics

Solid content:

Evaporation rate:

Further Information

Data apply to technical substance: Relative density, Colour, Odour, Viscosity, pH.

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol.

10.2. Chemical stability

The product is stable under normal conditions.

10.3. Possibility of hazardous reactions

Do not expose to temperatures above 50 °C. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air. Take precautionary measures against static discharges.

10.5. Incompatible materials

Oxidizing agents. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis gases of different toxicity can occur. In the case of hydrocarbonaceous products such as CO, CO2, aldehydes and soot. These can be very dangerous if they are inhaled in high concentrations or in enclosed spaces.

Further information

Do not mix with other chemicals.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

There are no data available on the mixture itself.

Acute toxicity

Based on available data, the classification criteria are not met.

not determined not determined

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 7 of 11

CAS No	Chemical name							
	Exposure route	Dose		Species	Source	Method		
75-28-5	isobutane							
	inhalation vapour	LC50	1237 mg/l	Mouse.				
68037-01-4	Dec-1-ene, homopolyme	r, hydrogenat	ted					
	oral	LD50 mg/kg	> 5000	Rat				
	dermal	LD50 mg/kg	> 2000	Rabbit				
	inhalation (4 h) aerosol	LC50 mg/l	> 5,2	Rat				
106-97-8	butane							
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS			
192268-65-8	A mixture of: triphenylthic	ophosphate a	nd tertiary b	utylated phenyl derivative	S			
	oral	LD50 mg/kg	>2000	Rat				
	dermal	LD50 mg/kg	>2000	Rat				
	inhalation (4 h) aerosol	LC50	>5 mg/l	Rat				

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met. No indication of human carcinogenicity. No indications of human germ cell mutagenicity exist.

No indications of human reproductive toxicity exist.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 8 of 11

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
75-28-5	isobutane						
	Acute fish toxicity	LC50 mg/l	91,42	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
68037-01-4	Dec-1-ene, homopolymer	, hydrogen	ated				
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss (Rainbow trout)		
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	> 1000	48 h	Daphnia magna		
74-98-6	propane	-		-	-	-	Ŧ
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
106-97-8	butane						
	Acute fish toxicity	LC50 mg/l	49,9	96 h	Fish, no other information	United States Environmental Protection A	The Ecosar class program has been develo
	Acute algae toxicity	ErC50 mg/l	19,37	96 h	Algae	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
	Acute crustacea toxicity	EC50 mg/l	69,43	48 h	Daphnia sp.	USEPA OPPT Risk Assessment Division (200	Calculation using ECOSAR Program v1.00.
192268-65-8	A mixture of: triphenylthio	phosphate	and tertiary b	outylated	phenyl derivatives		
	Acute fish toxicity	LC50 mg/l	>100	96 h	Danio rerio (zebrafish)		
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Scenedesmus subspicatus		
	Acute crustacea toxicity	EC50 mg/l	>100	48 h	Daphnia magna		

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 9 of 11

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	1,09
74-98-6	propane	1,09
106-97-8	butane	1,09

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - used product

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1
Classification code:	5F
Special Provisions:	190 327 344 625
Limited quantity:	1 L
Excepted quantity:	E0
Transport category:	2
Tunnel restriction code:	D
Inland waterways transport (ADN)	
14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
<u>14.3. Transport hazard class(es):</u>	2

according to UK REACH Regulation

90	902 Synthetic Oil Fluid MP90200400AB				
Revision date: 29.06.2021	Product code: 1101544	Page 10 of 11			
14.4. Packing group:	-				
Hazard label:	2.1				
Classification code:	5F				
Special Provisions:	190 327 344 625				
Limited quantity:	1L				
Excepted quantity:	E0				
Marine transport (IMDG)					
14.1. UN number or ID number:	UN 1950				
14.2. UN proper shipping name:	AEROSOLS				
14.3. Transport hazard class(es):	2.1				
14.4. Packing group:	-				
Hazard label:	2.1				
Marine pollutant:	no				
Special Provisions:	63, 190, 277, 327, 344, 381,959				
Limited quantity:	1000 mL				
Excepted quantity: EmS:	EO				
-	F-D, S-U				
Air transport (ICAO-TI/IATA-DGR)					
<u>14.1. UN number or ID number:</u>	UN 1950				
14.2. UN proper shipping name:	AEROSOLS, flammable				
14.3. Transport hazard class(es):	2.1				
14.4. Packing group:	-				
Hazard label:	2.1				
Special Provisions:	A145 A167 A802				
Limited quantity Passenger:	30 kg G				
Passenger LQ:	Y203				
Excepted quantity:	E0				
IATA-packing instructions - Passenger: IATA-max. quantity - Passenger:	203 75 kg				
IATA-max. quantity - Passenger. IATA-packing instructions - Cargo:	75 kg 203				
IATA-max. quantity - Cargo:	150 kg				
14.5. Environmental hazards					
	No				
ENVIRONMENTALLY HAZARDOUS:	No				
<u>14.6. Special precautions for user</u> Warning: Flammable gases.					
14.7. Maritime transport in bulk according t	o IMO instruments				
not applicable					
SECTION 15: Regulatory information					
15.1. Safety, health and environmental regu	lations/legislation specific for the substance or mixture				
EU regulatory information					
Restrictions on use (REACH, annex XVII)					
Entry 3, Entry 28					
2010/75/EU (VOC):	No information available.				
2004/42/EC (VOC):	No information available.				
Additional information					
Safety Data Sheet according to Regul	ation (FC) No. 1907/2006 (REACH)				
Aerosol directive (75/324/EEC)					

Aerosol directive (75/324/EEC)

according to UK REACH Regulation

902 Synthetic Oil Fluid MP90200400AB

Revision date: 29.06.2021

Product code: 1101544

Page 11 of 11

National regulatory information

Water hazard class (D):

1 - slightly hazardous to water

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 6,7,9,14.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA: International Air Transport Association IMDG: International Maritime Code for Dangerous Goods GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL/DMEL: Derived No Effect Level / Derived Minimal Effect Level WEL (UK): Workplace Exposure Limits TWA (EC): Time-Weighted Average ATE: Acute Toxicity Estimate STEL (EC) Short Term Exposure Limit LC50: Lethal Concentration EC50: half maximal Effective Concentration ErC50: means EC50 in terms of reduction of growth rate

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H361d	Suspected of damaging the unborn child.
H413	May cause long lasting harmful effects to aquatic life.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)